

Kyocera FS-6525MFP A3 MFD

908,000 AMD ~~1,365,400 AMD~~

GENERAL	
General type	Monochrome multifunctional for A4/ A3 format
Technology	KYOCERA ECOSYS, Mono Laser, HyPAS
Engine speed	Up to 25/12 pages A4/A3 per minute (print/copy)
Resolution	600 x 600 dpi (print), 600 x 600 dpi (scan/copy)
Warm-up time	20 seconds or less
Time to first print	Approx. 8 seconds or less
Time to first copy	Approx. 9.2 seconds or less (DP), 7.8 seconds or less (Platen Cover)
Dimensions (W x D x H)	590x590x694 mm (Dimensions with document processor)
Weight	Approx. 52.2 kg (Weight with document processor, including toner container)
Power consumption	Sleep-mode: 0.9 W, Ready mode: 114 W, Copying/Printing: 530 W
Power source	AC 220 ~ 240 V, 50/60 Hz
Noise (ISO 7779)	Copying/Printing: 46.8 dB(A), Stand-by: 27.1 dB(A)
Safety standards	TUV/GS, CE - This product is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.
General memory	1024 MB, max. 2,048 MB
PAPER HANDLING	
Input capacity	100-sheet multi-purpose tray, 45~256 g/m ² (52~163 g/m ² for larger than A4/Letter size): A3, A4, A5, A6, B5, Letter, Legal, Folio, envelopes, Custom (98 x 148 to 297 x 432 mm) 500-sheet universal paper cassette, 60~163 g/m ² , A3, A4, A5, B5, Letter,
Max. input capacity with options	1,600 sheets
Duplex unit	Duplex as standard supports 60~163 g/m ²
Max. output	Max. 300 sheets: 250 sheets face-down (main tray), plus 50 sheets (job separator)
Document processor	Reversing document processor: 50-sheet, Simplex scan 45~160 g/m ² , Duplex scan 50~120 g/m ² , A3, A4, A5, B5, Letter, Legal, Custom (140x182 to 297x432mm)
General paper handling	All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.
PRINT	
Processor	PowerPC 464 - 800 MHz
Controller language	PRESCRIBE IIe
Emulations	PCL 6 (5e/XL), KPDL3 (Postscript 3 compatible), PDF Direct print, XPS Direct print
Fonts	93 outline fonts (PCL 6, KPDL 3) + 8 (Windows Vista), 1 Bitmap font, 45 types of one-dimensional barcodes, 1 type of two-dimensional barcode (PDF417)
Integrated	100 department codes
Features	Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3, Private Print

Standard Interfaces	USB 2.0 (Hi-Speed), USB Host 2.0, Fast Ethernet 10/100/1000Base-TX, slot for optional print server, slot for optional CompactFlash-Card
Resolution	600 x 600 dpi
Applicable OS	All current Windows operating systems, MAC OS X Version 10.4 or higher, Unix, Linux as well as other operating systems on request
COPY	
Copy resolution	600 x 600 dpi
Max. original size	A3/Ledger
Digital copy features	Scan-once-copy-many, electronic sort, 2in1, 4in1, job reserve, priority print, program, auto duplex copy, split copy, continuous scan, auto cassette change (PF-470 or PF-471 is required), copy density control, Prevent Bleed-Through
Exposure modes	Auto, manual: 7 steps
Preset magnification ratios	5 Reductions/5 Enlargements
Zoom range	25 - 400 % in 1% steps
Continuous copy	1 - 999
Image adjustments	Text, Photo, Text + Photo, Graphic/Map, Copy/Printout
SCAN	
Compression	MMR /JPEG
File type	PDF, PDF/A, JPG, TIFF, XPS
Scan features	Colour Scan integrated address book, Active Directory support, encrypted data transfer, multi send (e-mail, fax, SMB/FTP folder, print) at once
Original recognition	Text, photo, text + photo, optimized for OCR
Max. scan size	A3/Ledger
Scan functionalities	Scan-to-email, Scan-to-FTP, Scan-to-SMB, Scan to USB Host, Network TWAIN, WIA, WSD scan
Scan resolution	200 dpi, 300 dpi, 400 dpi, 600 dpi (256 greyscales per colour)
Scan speed	40 ipm (300 dpi, A4, b/w), 20 ipm (300 dpi, A4, colour)
FAX	
Compatibility	ITU-T Super G3
Modem speed	Max. 33.6 kbps
Scanning speed	2.0 seconds (Quick Scanning, Bitmap)
Transmission speed	Less than 3 sec
Scanning density	Normal: 8 dot/mm x 3.85 line/mm, Fine: 8 dot/mm x 7.7 line/mm, Superfine: 8 dot/mm x 15.4 line/mm, Ultrafine: 16 dot/mm x 15.4 line/mm, Halftone: 256 gray scales
Max. original size	A3/Ledger
Compression	JBIG, MMR, MR, MH
Fax features	Network fax, duplex transmission and reception, encrypted transmission and reception, polling transmission and reception, broadcast
INTERFACES	
Standard interface	USB 2.0 (Hi-Speed), USB Host 2.0, Fast Ethernet 10/100/1000Base-TX, slot for optional print server, slot for optional CompactFlash-Card