

APC Smart-UPS SRT 2200VA 230V (SRT2200XLI) (s)

940,000 AMD

Output	
Output Power Capacity	1980 Watts / 2200 VA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Load Crest Factor	3 : 1
Topology	Double Conversion Online
Waveform Type	Sine wave
Output Connections	(8) IEC 320 C13 (Battery Backup) (2) IEC Jumpers (Battery Backup) (2) IEC 320 C19 (Battery Backup)
Bypass	Internal Bypass (Automatic and Manual)
Form Factor	Tower/Rack-Mount 2U
Input	
Nominal Input Voltage	230V
Input Frequency	40 - 70 Hz (auto sensing)
Input Connections	IEC-320 C20, Schuko CEE 7 / EU1-16P, British BS1363A
Cord Length	2.44 meters
Input voltage range for main operations	160 - 275V
Batteries & Runtime	
Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	3 hour(s)
Typical Backup Time at Half Load	11.6 min (990 Watts)
Typical Backup Time at Full Load	3.9 min (1980 Watts)
Replacement Battery	APCRBC141
RBC Quantity	1
Communications & Management	
Interface Port(s)	RJ-45 Serial, Smart-Slot, USB
Control panel	Multi-function LCD status and control console
Audible Alarm	Audible and visible alarms prioritized by severity
Emergency Power Off (EPO)	Yes
Available SmartSlot, & Interface Quantity	1
Surge Protection and Filtering	
Surge energy rating	340Joules
Filtering	---

Physical	
Maximum Height	43.2 cm
Maximum Width	8.5 cm
Maximum Depth	58.4 cm
Net Weight	25 kg
Environmental	
Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95% non-condensing %
Operating Elevation	0 - 3000 meters
Storage Temperature	-15 to 45 °C
Audible noise at 1 meter from surface of unit	55.0 dBA
Warranty	3 year warranty