

Yealink Professional IP Phone without PoE (SIP-T22)

55,000 AMD

Phone Features

- Â 3 SIP accounts
- Â Call hold, mute, DND
- Â One-touch speed dial, hotline
- Â Call forward, call waiting, call transfer
- Â Group listening, SMS
- Â Redial, call return, auto answer
- Â Local 3-way conferencing
- Â Direct IP call without SIP proxy
- Â Ring tone selection/import/delete
- Â Set date time manually or automatically
- Â Dial plan
- Â XML Browser, Action URL/URI
- Â RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)

IP PBX System Integration

- Â Busy Lamp Field (BLF)
- Â Bridged Line Appearance(BLA)
- Â Anonymous call, anonymous call rejection
- Â Hot-desking, emergency call
- Â Message Waiting Indicator (MWI)
- Â Voice mail, call park, call pickup
- Â Intercom, paging, music on hold
- Â Call completion, call recording

Codecs and Voice Features

- Â HD voice: HD handset, HD speaker
- Wideband codec: G.722
- Narrowband codec:Â G.711(AÎ¼), G.723.1, G.729AB,Â G.726, iLBC
- Â DTMF: In-band, Out-of-band(RFC 2833) and SIPÂ INFO
- VAD, CNG, AEC, PLC, AJS, AGC
- Full-duplex hands-freeÂ speakerphone with AEC

NetworkÂ and Security

- SIP v1 (RFC2543), v2 (RFC3261)
- NAT Traversal: STUN mode
- Â Proxy mode and peer-to-peer SIP link mode
- Â IP assignment: static/DHCP
- Â HTTP/HTTPS web server

- Â Time and date synchronization using SNTP
- Â UDP/TCP/DNS-SRV(RFC 3263)
- Â QoS: 802.1p/Q tagging (VLAN), Layer 3 ToSÂ DSCP
- Â SRTP for voice
- Â Transport Layer Security (TLS)
- Â HTTPS certificate manager
- Â AES encryption for configuration file
- Â Digest authentication using MD5/MD5-sess
- Â OpenVPN, IEEE802.1X
- Â IPv6

Management

- Â Configuration: browser/phone/auto-provision
- Â Auto provision via FTP/TFTP/HTTP/HTTPSÂ for mass deploy
- Â Auto-provision with PnP
- Â Zero-sp-touch, TR-069
- Â Reset to factory, reboot
- Â Package tracing export, system log

Physical Features

- Â 132x64-pixel graphical LCD with backlight
- Â LED for call and message waiting indication
- Â One-color (green) illuminated LEDs forÂ line status information
- Â Intuitive user interface with icons and soft keys
- Â National language selection
- Â Caller ID with name, number
- Â 2xRJ45 10/100M Ethernet ports
- Â Power over Ethernet (IEEE 802.3af), class 2
- Â 1xRJ9 (4P4C) handset port
- Â 1xRJ9 (4P4C) headset port
- Â Wall mountable
- Â External universal AC adapter (optional)ï¼šAC 100~240V input and DC 5V/1.2A output
- Â Power consumption (PSU): 1.4-2.0W
- Â Dimension(W*D*H*T):Â 209mm*188mm*150mm*41mm
- Â Operating temperature: -10~50Â°C

Warranty

- 1 year