

APC Smart-UPS SRT 10000VA 230V (SRT10KXLI)

[Coming Soon](#)

Output	
Output Power Capacity	10.0 KWatts / 10.0 kVA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Load Crest Factor	3 : 1
Topology	Double Conversion Online
Waveform Type	Sine wave
Output Connections	(6) IEC 320 C13 (Battery Backup) (4) IEC 320 C19 (Battery Backup) (1) Hard Wire 3-wire (H N + G) (Battery Backup) (3) IEC Jumpers (Battery Backup)
Bypass	Internal Bypass (Automatic and Manual)
Form Factor	Tower/Rack-Mount 6U
Input	
Nominal Input Voltage	230V , 400V 3PH
Input Frequency	40 - 70 Hz (auto sensing)
Input Connections	Hard Wire 3 wire (1PH+N+G), Hard Wire 5-wire (3PH + N + G)
Input voltage range for main operations	160 - 275V
Batteries & Runtime	
Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	1.5 hour(s)
Typical Backup Time at Half Load	11.5 min (5000 Watts)
Typical Backup Time at Full Load	3.8 min (10000 Watts)
Replacement Battery	APCRBC140
RBC Quantity	2
Communications & Management	
Interface Port(s)	RJ-45 10/100 Base-T , RJ-45 Serial , Smart-Slot , USB
Control panel	Multi-function LCD status and control console
Audible Alarm	Audible and visible alarms prioritized by severity
Emergency Power Off (EPO)	Yes
Available SmartSlot, & Interface Quantity	1
Surge Protection and Filtering	
Surge energy rating	480Joules
Physical	
Maximum Height	43.2 cm
Maximum Width	26.3 cm

Maximum Depth	71.5 cm
Net Weight	111.82 kg
Environmental	
Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95% non-condensing %
Operating Elevation	0 - 3000 meters
Storage Temperature	-15 to 45 °C
Audible noise at 1 meter from surface of unit	55.0 dBA
Warranty	3 year warranty