

Micronet VoIP FXO Gateway SP5052

121,900 AMD

Model	SP5052
Standard	ITU-T H.323
Interface	2 RJ-11 FXO ports for PSTN or PBX's extension line 1 10M RJ-45 port
LED Indication	System: POWER, READY, STATUS
Port: LINK, ACT, L1 - L2	
Voice	G.711A/? law, G.723.1, G.729 CODEC
	Voice Activity Detection (VAD)
	Comfort Noise Generation (CNG)
	Echo Cancellation
	Dynamic Jitter Buffer
DTMF	Bad Frame Interpolation
	In-band
	RFC2833
	H245 Alphanumeric
	H.245 Signaling
Telephony	q.931
	Call Hold / Call Forward
	Caller ID (Bellcore / ETSI FSK)
	Tone or voice greeting
	Polarity reversal detection
	Disconnect tone detection
FAX support	Phone address book
	FAX auto-detection
	G3 Fax relay (2.4 - 14.4 kbps)
	T.38
	T.38 ECM (SP5052 only)
	T.38 FAX Redundancy Depth
Networking	ASN.1 (SP5052 only)
	PPPoE dial-up
	DDNS (SP5054 only)
	DHCP client
	SNTP
NAT Traversal	TFTP/FTP client for firmware upgrade
	IP sharing
QoS	Outbound proxy (SP5052/S only)
	IP ToS / DSCP
Management	Web / Telnet / Console

Environment	Operating temperature: 0 - 40 degree C
	Storage temperature: -20 - 70 degree C
	Operating Humidity: 10% to 90%
Dimension & Weight	22cm x 4.4cm x 21.5cm (W x H x D), 2.3kg
Power Supply	100~240 VAC, 50~60 Hz
Emission	CE, FCC