

# APC Back-UPS 950VA (BX950UI)

79,500 AMD

<b>Output</b>	
Output Power Capacity	480Watts / 950VA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	50/60 Hz +/- 1 Hz
Waveform Type	Stepped approximation to a sinewave
Output Connections	(1) IEC Jumpers (Battery Backup) (6) IEC 320 C13 (Battery Backup)
<b>Input</b>	
Nominal Input Voltage	230V
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	IEC-320 C14
Cord Length	1.22 meters
Input voltage range for main operations	150 - 280V
Number of Power Cords	1
<b>Batteries &amp; Runtime</b>	
Battery Volt-Amp-Hour Capacity	76
Typical recharge time	8hour(s)
Typical Backup Time at Half Load	7.5 min (240 Watts)
Typical Backup Time at Full Load	1.3 min (480 Watts)
<b>Communications &amp; Management</b>	
Interface Port(s)	USB
Control panel	LED status display with On Line : On Battery : Replace Battery and Overload indicators
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
<b>Surge Protection and Filtering</b>	
Surge energy rating	273 Joules
<b>Physical</b>	
Maximum Height	215mm
Maximum Width	130mm
Maximum Depth	336mm
Net Weight	8.0 kg
<b>Environmental</b>	
Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95% non-condensing %
Operating Elevation	0-3000 meters
Storage Temperature	-15 to 45 °C
Audible noise at 1 meter from surface of unit	45.0 dBA

<b>Warranty</b>	2 year warranty
-----------------	-----------------