

Tripp Lite SUPER6OMNID 6 outlets Surge Suppressor

11,400 AMD

OVERVIEW	
Intended Application	Home/Office
OUTPUT	
Frequency compatibility	50 / 60 Hz
Circuit Breaker (amps)	10
Overload protection	10A resettable illuminated combo switch/circuit
Outlet quantity / type	6 universal outlets
Outlet orientation	right-angled
INPUT	
Nominal Input Voltage(s) Supported	230V AC
Recommended Electrical Service	230V (220-250V)
Input connection type	German
Input cord length (ft.)	6
Input cord length (m)	1.8
Voltage compatibility (VAC)	220-250
Maximum Surge Amps	13500
LEDS ALARMS & SWITCHES	
Switches	Two position power switch
SURGE / NOISE SUPPRESSION	
AC suppression joule rating	750
AC suppression response time	
Protection modes	Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression
DATALINE SURGE SUPPRESSION	
Telephone/DSL Protection	No
Cable (Coax) Protection	No
Network (Ethernet) Protection	No
PHYSICAL	
Shipping weight (kg)	0.60
Unit Dimensions (HWD/cm)	39.4 x 6.4 x 3.2
Shipping Dimensions (HWD/cm)	47.0 x 11.4 x 5.1
Unit weight (kg)	0.45
Material of construction	Plastic
Integrated keyhole mounting tabs	Yes - slotted
Housing Color	Light Gray
Receptacle Color	Light Gray

AC line cord color	light gray
Style	Strip
Outlets center to center measurement	51mm
Keyhole slot center to center measurement	219.5mm