

# APC Smart-UPS 1500VA LCD 230V (SMT1500I)

403,800 AMD

<b>Output</b>	
<b>Output Power Capacity</b>	1000 Watts / 1500 VA
<b>Nominal Output Voltage</b>	230V
<b>Output Frequency (sync to mains)</b>	47 - 53 Hz for 50 Hz nominal , 57 - 63 Hz for 60 Hz nominal
<b>Waveform Type</b>	Sine wave
<b>Output Connections</b>	(2) IEC Jumpers (Battery Backup) (8) IEC 320 C13 (Battery Backup)
<b>Input</b>	
<b>Nominal Input Voltage</b>	230V
<b>Input Frequency</b>	50/60 Hz +/- 3 Hz (auto sensing)
<b>Input Connections</b>	IEC-320 C14
<b>Cord Length</b>	1.83 meters
<b>Input voltage range for main operations</b>	151 - 302V
<b>Batteries &amp; Runtime</b>	
<b>Typical recharge time</b>	3 hour(s)
<b>Typical Backup Time at Half Load</b>	23 min (500 Watts)
<b>Typical Backup Time at Full Load</b>	6.5 min (1000 Watts)
<b>Replacement Battery</b>	RBC7
<b>RBC Quantity</b>	1
<b>Communications &amp; Management</b>	
<b>Interface Port(s)</b>	SmartSlot , USB
<b>Control panel</b>	Multi-function LCD status and control console
<b>Audible Alarm</b>	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
<b>Surge Protection and Filtering</b>	
<b>Surge energy rating</b>	459 Joules
<b>Filtering</b>	Full time multi-pole noise filtering: 0.3% IEEE surge let-through : zero clamping response time: meets UL 1449
<b>Physical</b>	
<b>Maximum Height</b>	219.0 mm
<b>Maximum Width</b>	171.0 mm
<b>Maximum Depth</b>	439.0 mm
<b>Net Weight</b>	24.09 kg
<b>Environmental</b>	
<b>Operating Environment</b>	0 - 40 °C
<b>Operating Relative Humidity</b>	0 - 95%

<b>Operating Elevation</b>	0-3000 meters
<b>Storage Temperature</b>	-15 to 45°C
<b>Audible noise at 1 meter from surface of unit</b>	45.0 dBA
<b>Warranty</b>	3 year warranty