

Epson EB-G5100 Projector

1,464,700 AMD

General	Aspect Ratio	4:3 (Native) 16:9
	Brightness (ANSI Lumens)	4000 ANSI Lumens (High Brightness Mode) 3200 ANSI Lumens (Low Brightness Mode)
	Contrast Ratio	1000:1
	Display Type	0.8" PolySilicon TFT Active Matrix LCD x 3
	Resolution (Native / Max)	XGA (1024 x 768) UXGA (1600 x 1200)
	Video Compatibility	NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, PAL 60, SECAM, HDTV (480i, 480p, 576i, 576p, 1080i)
	Projection Lens	F = 1.6 ~ 2.5 f = 21.3 ~ 37.9mm
	Number of Colors	16.77 Million Colors
Size	Dimensions (WxHxD)	18.5in. x 5.3in. x 12.3in. (46.99cm x 13.46cm x 31.24cm)
	Weight	14.5 lbs. (6.58 kg)
Connectivity	Inputs	1 x RGB D-Sub 15pin 1 x Stereo Mini Jack 5 x BNC 1 x Composite 1 x S-Video 2 x Component 1 x RCA Audio 1 x HDMI
	Outputs	2 x RGB D-Sub 15pin 1 x Stereo Mini Jack
	Audio	1 x 7W Monaural Speaker
	Control	1 x RS-232C 1 x RJ-45
Operation	Power Supply	100 ~ 120 / 220 ~ 240 V / 50 ~ 60 Hz
	Power Consumption	343W (Normal) 0.4 (Standby)
	Audible Noise	35 dB (High Brightness Mode) 29 dB (Low Brightness Mode)
	Operating Temperature	32Â°F ~ 104Â°F (0Â°C ~ 40Â°C)
	Operating Humidity	20 ~ 80% (Non-Condensing)

Projection Lens	Lamp Type	210W UHE
	Lamp Life	2000 hrs (High Brightness Mode) 3000 hrs (Low Brightness Mode)
	Lens Shift	Vertical: +/- 50% Horizontal: +/- 10%
	Projection Distance	2.5ft. ~ 26.5ft. (0.76m ~ 8.08m)
	Projection Mode	Front, Rear, Ceiling
	Projection Screen Size (Diagonal)	30in. ~ 300in. (76.2cm ~ 762cm)
	Optical Zoom	1.8:1
	Horizontal Keystone	+/- 10 Degrees
	Vertical Keystone Correction	+/- 50 Degrees
Other	Dot Clock	13.5 ~ 162 MHz
	H-Sync Range	15 ~ 99 kHz
	V-Sync Range	50 ~ 120 Hz
In The Box	Items	Power Cord PC Cable Batteries Remote Control Password Protection Sticker Epson Projector Software

v